

A Study of Financial Aspects Using The Jet Spinner System in the Textile Industry

Dr. Ir. Raden Achamad Harianto M.M.(First Author), Pratiwi Nila Sari, M.Ak, CPA (Co Author)

¹(University Of Bayangkara Jakarta Raya) Faculty of Economics, Department of Management & Business, Bekasi, Indonesia; ²(University of Bhayangkara Jakarta Raya) Faculty of Economics, Department of Accounting, Bekasi, Indonesia. Email: raden.achmad@dsn.

ABSTRACT

The objective of the research are to study in comparing of financial aspect between Ring Spinning and Jet Spinner in a study with assumption that the spinning factory is established to meet the standard completely, large size and construction are ideal, and the factory areal is feasible for the

instalation of the mechinery with full running.

The research was conducted at PT. Argopantes in Spinning factory unit III. Method used in this research is the descriptived Qualitative, the technique of collecting data are observation and interview.

The result of the investigations show that A Study of the financial aspects get a profit in Jet Spinning sistem as follows: (1) The Jet Spinner process is more simple than ring spinning, (2) The production is going up, (3) there is the productivity addition and cost down, and (4) the reduction of production cost.

Based on the study findings it could be concluded that the Jet Spinner processing improve the efficiency in yarn quality and cost down than the Ring Spinning

Keywords: Study; Financial Aspects; Jet Spinner; Styling; Industry.

1 INTRODUCTION

Judging from the factors that influence the spinning process of Jet Spinner machines from a study of the financial aspects. There are many factors that are related to the cost of production in making threads using the Jet Spinner system yarn from one country to another is very different, and this is depends on the conditions climate of each country. Apart from this problem, the author will examine this paper in a limited context in terms of data. Studied based on a comparative study between the Jet Spinner spinning system and Ring Spinning, so this study will provide a fairly valid and reliable picture.[1], [9], [10]

To conduct this comparative study, it is first assumed that the things that need to be considered are [3]:

- 1. The spinning mill built is quite complete to meet the standards.
- 2. The size and shape of the building is quite ideal.
- 3. The area of the factory is quite feasible so that there is a continuity of the engine

installed with a full (large) workload in several ways.

From the background of the above problem, it can be formulated that: What are the financial aspects of the textile industry in the yarn spinning department, if the production cost of a Jet Spinner machine is compared to a Ring Frame machine ? [4]

2. Material and Methods

2.1. Research Material

The results of the "Shirley Institute" study show that the layout of the machine factories must be able to produce around 455 kg per hour, and this for 50 Tex threads [2].

IEEE-SEM, Volume 7, Issue 10, October-2019 ISSN 2320-9151

The Lay Out Plant in the spinning III factory of PT. Argopantes, it appears that the process that does not change is the engine unit from the bale store to the drawing frame, while the others change. If there are 4 Roving Frames, 25 Ring Frames and Mach Coner can be eliminated only by 24 sets of Jet Spinner machines.[4] and [5]'

The Jet Spinner system, especially in the case of a lot of bribery, takes place mostly compared to the ring frame system, because here uses cans, but when looking at the balance about eliminating Speed Frame and Winder, the things associated with taking more places are not problem, especially if it is associated with a high amount of production. [5], [6], [8], In order to be clearer about the information regarding this matter, it can be seen in table 1 and table 2 below.

Table 1: Properties of Yarn Spinning Results of JET SPINNER

Properties of Yarn	Compared to Ring Spinning (Spun Yarn)		
Average of Production	3 - 3.5 times		
Great Rolls	20 times		
Number (Tex)	20 - 60 (5 - 600 on the Frame Ring)		
Antihan / Twist / Twisting	10-15% higher		
Average Strength	15 - 20% weaker		
Variation in strength	Less		
Extensibility	10% higher		
Work of rupture (WOR)	Same		
Regularity	10-20% better		
Number Variation	Better		
Appearance	More uniform 10% greater than the specific volume		
Bulkiness			
Surface	More smooth and slippery		
Fur	20 - 40% less		
Cleanliness	Better		
Nep	Less		
Thread error	80% can be reduced		
Stability	Better		
Hold rub	20 - 30% better		
Handle	More rough		
Mixing Fiber	Better		
Dyeing results	Good (more alive)		
Thread Disconnect	75% can be reduced		

Table 2: Characteristics of Using Fabrics made from Jet Spinner Yarn

Properties of Yarn	Compared to Ring Spinning (Spun Yarn)		
Disconnect threads in Reeling	50% reduced		
Splicing (after rolling)	15-17 / kg decreases		
Broken heart in weaving	70% decreases		
Break the feed at Weaving	25% reduced		
Strength (Pull, Tear, Broken)	Reduced		
Appearance	More uniform		
Closing Power	10% better		
Cleanliness	Better		
Heat Insulation	10 - 5% better		
Air Permeability	10 - 25% better		
Water absorption	Better		
Shrinkage	Same		

Dipping power	Better
Raising	Easier and more evenly distributed

From Table 1 and Table 2 it appears that the production produced including other factors shows a positive level of improvement. For example, the average production is almost 3.5 times. For certain conditions, the factory capital costs regarding Jet Spinner machining are 5-10% higher but there will be a very significant difference when processing finer threads. In addition, the production working time for Jet Spinner can be up to 168 hours per week, while for the Ring Frame 112.5 hours. This fact resulted in investment in spinning mills with Jet Spinner machines to date attracting many scientists and entrepreneurs. But until now the textile industry entrepreneurs still face difficulties in making decisions whether to continue to use the ring frame machine along with the simplex and winder machines, or to use the super high draft system through the Jet Spinner engine in terms of its economic aspects. To provide accurate information for textile industry entrepreneurs in strategic decision making, research and assessment needs to be carried out through comparative studies on economic aspects in the Jet Spinner yarn spinning industry. [2].

2.2. Research Methods

The Quantitative research is carried out using descriptive methods. Comparative studies between the production costs of Jet Spinner machines and the operating costs of Ring Frame machines are reviewed from their financial aspects. The method of data collection is done through field surveys, factory documentation, observation and interviews. The location of this research is PT. Argopantes in Spinning III Unit, which is on the Perintis Kemerdekaan Highway in Tangerang, for 2 months in November and December 2016

2.3. The Research Purposes

This applied research was conducted with the aim of knowing the ratio of production costs between the operation of the Jet Spinner machine and the operation of the Ring Frame machine in terms of financial aspects. [1], [9] and [10]

2.4. Benefits of Research

The benefits of this research are as reference information for the President or Textile Industry company leaders in strategic decision making, namely whether to buy yarn products or use Jet Spinner machines or Ring Frame machines in one package with Speed Frame machines and Mach Coner Winder machines. [4] and [9]

3. Results

3.1. The Operation Cost

Depreciation of machinery is proportional when it is associated with capital costs, if the existing risks (past) are considered non-existent. Depreciation and maintenance of buildings are also calculated rationally in relation to the location. Machinery and factory building insurance is also proportionally related to the first investment (origin). As for the amount (quantitatively from the value of raw materials) in the work process all the same for depreciation and insurance.

In general, the material fed on the Jet Spinner machine requires product quality that must be good, so it needs more careful consideration for the process. Unlike the process on the Ring Frame which only has 3 functions of the work process, namely drafting, twisting, and winding there are not many problems in the process, such as the Jet Spinner machine that takes over the tasks of Simplex, Ring Frame, and Winder machines that

In the Ring Frame spinning process, the amount of waste that occurs in the Roving / Simplex engine is 2%, and 2% in the Ring Frame process, while the process in Jet Spinner produces 1.5% waste. Realization of profits to 2.5% for the waste of the Jet Spinner process, in other words there is an emphasis in the amount of waste produced. When associated with additional money savings, it is clear that there is an addition by reducing waste by 2.5% during the process with the Jet Spinner system. Emphasis on process costs is very effective while production itself continues to increase. [4] and [10]

3.2. The Energy Use

Research that the author did at PT. Argo Pantes points out, with the energy that has been used in running the Jet Spinner engine is dissipated in the form of empty loads; the following equation is an empirical approach, namely: The energy to run the Rotor-rotor is: [4]

 $(D) = (3.5 \times 10 - 12) \text{ N } 2.5 \text{ DR } 3.8 \text{ W}$, where DR is the outer diameter of the rotor in units of inches and N is the rotor speed (RPM).

	1	1		
Linear Density (Tex)	60	35	25	15
Yarn Number (Ne)	10's	16's	24's	36's
Fixed Cost :				
- Room	1,3	2,4	4,1	6,4
- Insurance	-0,3	-1,2	-4,2	-8,1
- Material	0	0	0	0
Operation Cost :				
- Waste	13,7	13,7	13,7	13,7
- Power (Energy)	16,7	14,5	10,6	-3,1
- Operator (labour)	32,4	45,1	63,1	94,3
	63,8	74,5	87,3	-103,2
+ Capital Cost	-4,8	-23,2	-83,4	-161,2
++ Annual Net Savings with Jet Spinner				
	59,0	51,3	3,9	-58,0

Table 3 : Annual Spinning Savings of Jet Spinner System (£'000)

The transmission efficiency is very low (about the same as the Ring Frame), then the equation above becomes:

 $D = (8.2 \times 10 - 12) \times 2.5 DR 3.8 W$ Where the transmission value is calculated.[4]

From this equation, it shows the direct effects on the magnitude of the rotor diameter and speed. For Example:

If the rotor diameter is reduced to 50% of its origin, and the speed is increased by almost three times, then the energy spent remains the same as the original condition.

3.3. Engine Efficiency

Since spinning Jet Spinner is a new process, all machines from the form of modern design and stop motion equipment are further enhanced, such as doffing time equipment and others - related to efforts to increase efficiency.

Because the rolls of the product are large, the doffing time is increasingly rare, which means the engine rarely stops (efficiency can be improved).

Disconnect threads rarely and less than threads produced on the Ring Frame, and when the thread breaks, the process automatically stops. So there is no missing machine load. The breaking time in the machine is used to clean up the dirt found in the roto-rotor groove.

When the engine is stopped, the risk of breaking the thread is very small, especially when the engine is restarted after being stopped. This happens because of the automatic equipment that holds the threads during the process. Due to the large form of yarn produced, there is a reduction in duty / work handling in doffing (infrequent or extended doffing) and this is a labor saving where this free working time can be used for cleaning or other work related to the scope of Jet Spinning machines.

Capital savings can be further enhanced by the elimination of drawing, speed frames and winding processes and for other businessmen / investors who are not less interesting is the state of their employees' salaries (of course salary at Spinning of the Ring Frame is different from salary in the Spinning of Jet Spinner). [2] and [4].

3.4. Cost Balance

From studies that have been carried out, the Jet Spinner spinning system has 2 economic perspectives, namely those that are advantageous and those that are not profitable if this is all compared to spinning ordinary spinner jets. [4].

In table 3 below, we can see an illustration of the cost balance between spinning Jet Spinner and Ring Frame systems.

+ Average cost (expense) = 20% of the engine cost

++ Without detailed calculations (rough calculations) of possible savings

reserved is in the Winding process like Mach Coner.

Note:

The average production of 1,000 lbs per hour (455 kg / hour) the machine works 3 shifts.

From the illustration above, it can be seen that the Jet Spinner spinning system will be very good for making coarse to medium threads (type of Jet spin with Splicer at a speed of 40,000 - 80,000) and BEP (Break Even Point) values will be obtained in making 24 tex threads (25's Ne). In practice, every day BEP will be more likely to be pressed again at the level of making 37 tex threads.

4. Discussion

4.1. The Advantages of a Jet Spinner Spinning System

If you see the results of the production of the Jet Spinner machine that is the shape of a large Cones and this shape is almost the same as the product of the Winding machine. In fact, it is clear that the Jet Spinner engine will shorten a series of processes, even at present, there are many preparation processes for weaving machines whose threads are supplied by thread cones from the production of Jet Spinner machines. As is known, in terms of product efficiency, in the Winding machine, it is larger than the roll, and it is also higher than the productivity value, and for this, from the Jet Spinner engine whose large roll can neutralize the situation, so it can match the results of Winding engine products. [5], [6], and [8].

In other words, the production of the Jet Spinner engine is really able to increase production both in terms of quality and quantity, also shorten the work process by not eliminating the quality aspects of the product desired by consumers.

5..CONCLUSION

Financial aspects that are beneficial in the Textile Industry with Jet Spinner system, it can be concluded, that:

- 1. A long series of spinning processes can be simplified.
- 2. Yarn production capacity can be increased
- 3. Increased work productivity can save costs.
- 4. Production costs can be saved.

From the results of the research described above, it can be recommended that: both the Entrepreneurs / Stake Holders and the President Director / CEO can choose the Jet Spinner machine if you want to make a thread under 25 tex, and if you want to make fine yarn above 25 tex > Ne1 40 can choose the Ring Frame engine simultaneously with the Flyer / Simplex engine and the Mach Coner machine.

ACKNOWLEDGMENT

The author is deeply grateful to Prof. Moekarto Moeliono, formerly of the Department of Textile Technology, Bandung Textile Institute of Technology, for his advice during the course of the work reported here and to Tangerang Industrial Estate Cikokol for supplying the data and information used in the studies.

The author is deeply grateful to Prof. Moekarto Moeliono, formerly of the Department of Textile Technology, Bandung Textile Institute of Technology, for his advice during the course of the work reported here and to Tangerang Industrial Estate Cikokol for supplying the data and information used in the studies.

REFERENCES

- [1] Eddy Herjanto, (2009), "Manajemen Produksi & Operasi," Publisher : PT. Gramedia Widiasarana Indonesia, Jakarta.
- [2] Elliot B. Grover and D.S. Hamby, (1969). "Handbook of Testing and Quality Control", John Wiley & Sons, New York.
- [3] Husein Umar (2009). "Studi Kelayakan Bisnis", Manajemen, Metoda, & Kasus. Publisher : PT. Gramedia Pustaka Utama, Jakarta.
- [4] Moeliono, M. (1998). "Arena Tekstil No. 7", Publisher : Balai Besar Tekstil Bandung.
- [5] Murata (1990). "Hand Book of Jet Spinning System," Murata Co. Ltd., Japan.
- [6] Nield R (1995)., "Open End Spinning" The Textile Institute Manchester, Textile Institute Monograph Series.
- [7] Trijono B (2000)., "Study Kecepatan Rotor dan Rol Penyisir terhadap Mutu Benang", BD 200 BS TOYODA.
- [8] Vaclav Rohlena, et. Al. (1995)., "Open End Spinning". Elsevier Scientific Publishing Co, Amsterdam.
- [9] Shigeru Watanabe (2004), "Textile Technology," Published and Printed by Dainippon.
- [10] Sofyan Assauri, (2016). "Manajemen Operasi Produksi", Publisher : PT. Raja Grafindo Persada, Jakarta.

57